



LAST USED LIST

SYS.	36-50 & 86-100	CH.1 1-35	CH.2 51-85
A	4		
C	50	13	63
D	45	7	57
H	2		
Q	38	14	64
R	50 & 86	31	81
T	1		
Z	39	3	53
P		1	51

- 9 ADJUST P1/P51 FOR 75mA (±25mA) IDLE CURRENT UNIT WARM. 120 VAC LINE.
 - 8 S4 IS A THERMAL CUTOFF SWITCH, LOCATED ON HEATSINK (85° C CUTOFF).
 - 7 T1 IS: 15- FOR FET400 AMPS.
 - 6 ADDED AS SECONDARY OPERATIONS.
 - 5. A3 AND A4 ARE 4558 TYPE OP AMPS.
 - 4. A1 AND A2 ARE MC33078 OP AMPS.
 - 3. ALL DIODES ARE 1N4003 (EXCEPT AS NOTED).
 - 2. ALL CAPACITORS IN MICROFARADS (EXCEPT AS NOTED).
 - 1. THERMISTOR MUST BE IN CONTACT WITH HEATSINK.
- NOTES: UNLESS OTHERWISE SPECIFIED.

CARVIN		1155 INDUSTRIAL AVE. ESCONDIDO, CA. 92025 (619) 747-1710	
FET400 POWER MODULE			
DRAWN: S. MC KENNA	DATE: 22 MAR 88		
APPROVED:	DATE:		
Assembly NO: 80-04028	REV: G		
DWG NO: 84-04028	LAST PCN / DATE: #324 / 11 APR 89		
LAST SCHEMATIC UPDATE: 17 APR 89			