



△ RESISTORS ARE MILLEN BRADLY 10% V.L.V.  
 † A THING DENOTES AUDIO LEVEL TEST POINTS.

⊕ DESIGNATES WIRE TERMINATION.

1. ALL CAPACITORS ARE RATED AT 100V, ALL OTHER CAPACITORS ARE RATED AT 50V DC, UNLESS INDICATED OTHERWISE - 20% + 150%.

2. ALL COMPONENTS VOLTAGE VALUES ARE MINIMUM, ONLY HIGHER VOLTAGE VALUES MAY BE USED.

3. ALL COMPONENTS ARE MOUNTED ON PC BOARD.

4. LABS' REFERENCE DESIGNATIONS USED R3A, C47, CR2, Q11, Q12, Q13, Q14 AND LDR 1, OMITTED C.V1.

5. ALL RESISTORS ARE 1/4 WATT, VALUES IN OHMS ARE Ω.

NOTES: UNLESS OTHERWISE SPECIFIED.

— SCHEMATIC —			
PRE-AMP, SOLID STATE			
NO STYLE SWITCH AMP			
REV. NO.	REV. DATE	REV. NO.	REV. DATE
1	3-5-77	056358	C
DATE	REV.	REV.	REV.
NO. NONE	NO. SEVERAL	NO. /	NO. /