



1. ALL RESISTORS ARE $\frac{1}{2}$ WATT, VALUES IN OHMS $\pm 10\%$. NOTE: UNLESS OTHERWISE SPECIFIED.
2. ALL CAPACITORS ARE RATED AT 50V DC, VALUES IN MICROFARADS $\pm 20\%$, ELECTROLYTIC - 20% \pm 150%.
3. LAST REFERENCE DESIGNATIONS USED, R17, C10, CR10, Q5, T1, P1, J5, S2, F2, CB1, AND DS1. (OMITTED S1 AND P1)
4. ALL COMPONENT VOLTAGE VALUES ARE MINIMUM ONLY HIGHER VOLTAGE VALUES MAY BE USED.
5. ALL COMPONENTS ARE MOUNTED ON PC BOARD.
6. COMPONENT MOUNTED ON CONTROL PANEL.
7. COMPONENT MOUNTED ON CHASSIS.
8. COMPONENT MOUNTED ON HEATSINK.

Super 11

Pro & Super Reverb

P/N 109694

DRAWING TITLE - SCHEMATIC -			
POWER OUTPUT AMP-50W			
DES. 1170	SIZE B	DWG. NO. 076885	REV. F
SCALE NONE		SHEET 1 OF 1	

SR 2050
SR 4050