



NOTES:
 DOTTED LINES DENOTE WIRES OFF THE PCB.
 P1 = PAGE 1.
 E4 = GRID REF. E4.

ADJUST BIAS TO -50VOLTS APPROX (NO SIGNAL CONDITION)
 * NOT FITTED TO COMBOS

U.S.A ONLY
 SET BIAS TO -4.2 VOLTS.
 MAINS SUPPLY = 117V/60HZ
 (NO SIGNAL CONDITION)

ISS	ECD NUMBER	DATE	A	B	C	D	E	F	G
11	0715	22-09-94							
10	0665	24-09-94							
9	0663	25-07-94							
8	0452	14-1-94							
7	0450	14-12-93							

UNSPECIFIED HOLE DATA		MATERIAL		DIMENSIONS IN	
		MATERIAL THICKNESS		TOLERANCE (UNLESS OTHERWISE STATED)	
		INTERNAL BEND RADIUS		DIMENSIONAL	
		EXTERNAL B/A		CENTRES	
		BEND DIE		ANGULAR	
				MODEL	
				4100	

		TITLE	
		POWER AMP CCT	
COPYRIGHT BASED ON THIS DOCUMENT IT MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED AND MUST NOT BE REPRODUCED OR IN PARTS WITHOUT THE WRITTEN PERMISSION FROM MARSHALL AMPLIFICATION PLC DENNIS ROAD, BLETCHLEY, MILTON KEYNES, MK2 1SQ. TEL: 1200 870411 FAX: 1200 871116		2 OF 2 DWG.No 4100-60-02	ISSUE 11