



V1 FILAMENT:  
 5.2-5.5 VDC  
 FILAMENT CURRENT:  
 45 +/- 10 mA DC  
 V2 ELECTRODE SOURCE:  
 24-26 VDC TYP.  
 ELECTRODE CURRENT:  
 14 +/- 3.0 mA DC  
 BALLAST RESISTOR:  
 1K TYP.  
 ELECTRODE RUNNING VOLTAGE:  
 10 +/- 3.0 V DC  
 TOTAL LAMP WATTAGE:  
 .40 TYP.  
 INTENSITY  
 .1mW/Cm2 @ 351nm (REF.)  
 LIFE HOURS:  
 \*10,000

\*TO 50% OUTPUT INTENSITY

NOTE: CLEAR GLASS

JKL PART NO.: BGF717-UV351

	METRIC	DIMENSIONS ARE IN MILLIMETERS		<b>COMPONENTS CORPORATION</b>				
	THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED					TITLE	MINIATURE HOT CATHODE FLUORESCENT UV 351nm LAMP (ACORN)
	1 PL +/- 0.2	2 PL +/- 0.20	ANGLE +/- 0	SIZE	FSCM NO.	DRAWING NO.		
RELEASE & CANCEL P-0402-06	6/30/04	L. WENGSTROM	J.K. 6/30/04	<b>A</b>	<b>55335</b>	<b>BGF717-UV351</b>		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING -	SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET 1 of 1
			MANUAL REVISIONS NOT PERMITTED	NONE	6/30/04			