

Specifications

From Pickupedia

PICKUP SPECIFICATIONS

The intent is to provide information for builders by specifying known pickups by wire gauge, winding count, magnet type and orientation, and form factor.

Description	Core Length	Core Width	Core Height	Bobbin Flange	Gauge	Diameter	Ohms/1kft	Rdc Ω	Winds	Magnet
Jazz Bass Bridge	2.7770	0.1875	0.4920	0.6290	42.0	0.0028	1659	7250	8700	
Jazz Bass Neck	2.6500	0.1875	0.5310	0.4370	42.0	0.0028	1659	7500	8700	
P90 Lollar	2.2500	0.2500	0.2500	1.1250	42.0	0.0028	1659	8000	10000	
P90 WD	2.1850	0.2500	0.2500	1.1850	42.0	0.0028	1659	8000	10000	
PAF 59 Bridge Duncan	2.2250	0.2600	0.2500	0.7000	42.0	0.0028	1659	3715	5000	
PAF 59 Neck Duncan	2.2250	0.2600	0.2500	0.7000	42.0	0.0028	1659	4065	5000	
Rickenbacker Toaster	2.165	.26	.185	.93	44	0.0022	2593	6060	5000	A2 rod
Rick Toaster #2	2.165	.26	.185	.93	44	0.0022	2593	7400	6000	A2 rod
Rick Toaster #3	2.165	.26	.185	.93	44	0.0022	2593	8300	6500	A2 rod
Rick Toaster #4	2.165	.26	.185	.93	44	0.0022	2593	11000	8000	A2 rod
Strat 1954 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5760	7956	
Strat 1955 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5890	7844	
Strat 1956 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5980	8012	
Strat 1957 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6020	8105	
Strat 1958 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6200	8350	
Strat 1959 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5950	7925	
Strat 1960 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6330	8293	
Strat 1961 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6190	8119	
Strat 1962 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6220	8220	
Strat 1963 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6370	8319	
Strat 1964 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	6250	7980	
Strat 1965 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5800	7626	
Strat 1966 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5760	7630	
Strat 1967 Fender	2.2500	0.1875	0.4360	0.6250	42.0	0.0028	1659	5880	7656	

Tele Bridge 50-51	2.3785	0.1875	0.5000	0.7620	43.0	0.0025	2143	8000	8000
Tele Bridge 51+	2.3785	0.1875	0.5000	0.7620	42.0	0.0028	1659	7500	9200
Tele Bridge 60-70's	2.3785	0.1875	0.5000	0.7620	42.0	0.0028	1659	6400	7800
Tele Bridge Barden	2.3750	0.0625	0.5000	0.2550	43.0	0.0025	2143	2281	2400
Tele Bridge Duncan	2.3785	0.1875	0.5310	0.7620	43.0	0.0025	2143	7200	8000
Tele Bridge Lollar	2.3785	0.1875	0.5310	0.7500	43.0	0.0025	2143	7500	8000
Tele Neck 50's	2.1555	0.1875	0.4700	0.5000	43.0	0.0025	2143	7700	8000
Tele Neck 60's	2.1555	0.1875	0.4700	0.5000	43.0	0.0025	2143	6900	7800
Tele Neck Barden	2.1250	0.0625	0.5000	0.2220	43.0	0.0025	2143	2062	2400
Tele Neck Duncan	2.1555	0.1875	0.4700	0.5000	42.0	0.0028	1659	7700	8000
Tele Neck Lollar	2.1555	0.1875	0.4700	0.5000	43.0	0.0025	2143	6800	7800

Retrieved from "<http://pickupedia.info/Specifications>"

- This page was last modified on 31 December 2007, at 18:02.