

SPEC. CHART FOR GRETSCH PICK UP**1-Apr-03**

	<u>MAGNET</u>	<u>POLEPIECES</u>	<u>MAGNET WIRE</u>	<u>TURNS</u>	<u>POWER</u>	<u>SOUND</u>
Standard FilterTron	Ferrite (370H) 60 x 6 x 12.5	(-) 3.5 x 18.5 (mm)	Urethane 3UEW 0.05	3600T x 2	8 ± 0.5KΩ	STANDARD
Vintage FilterTron	#5 Alnico 58 x 3.2 x 12.5	(-) 3.5 x 18.5 (mm)	Urethane 0.063	3000T x 2	4KΩ	SWEETER HIGHS
Hot Rod	Supplied parts 0514-4V Alnico Magnet	Supplied parts 0514-4Z Fillister Head	Supplied parts #42 Enamel Magnet Wire	Neck : 2950T * Bridge : 3050T *	4.1 - 4.15 KΩ 4.3 - 4.38KΩ	HOT & SMOOTH
with (*) for Hot Rod Model : featurers to have special winding for Neck and Bridge PU.						
Bass FilterTron	Ferrite (370H) 60 x 6 x 12.5	(+) 3.5 x 16 (mm)	Urethane 3UEW 0.05	3600T x 2	8 ± 0.5 KΩ	
Dynasonic	#5 Alnico	#5 Alnico	Urethane 3UEW 0.05	5800T	8 ± 0.5 KΩ	CLEAN & PUNCHY
Hi-Lo Tron	Supplied parts 0514-4V Alnico Magnet	(-) 3.5 x 18 (mm)	Urethane 3UEW 0.05	Neck : 3200T Bridge : 3600T	3.4 - 3.6 KΩ 3.9 - 4.1 KΩ	CLEAN & SWEET
Single coil, alnico magnet, fairly low output, very sweet sounding. She loves you yeah, yeah, yeah !!!						
High Power	#5 Alnico 58 x 3.2 x 12.5	Supplied parts Socket Cap Screws	Urethane 0.063	Neck : 4000T Bridge : 5500T	8.8 KΩ 12.5 KΩ	HOT & THICK