

Shipping Instructions

- For the safest possible return to KRK, please use the shipping carton and packing that your Rokit Powered was originally shipped in.
- KRK cannot be responsible for any damages incurred during the shipping process due to poor packing. Make sure to insure your shipment.

- If your monitor is out of warranty and you would like a quotation prior to servicing your product, please call for an "RMA" number. No service will be performed on your unit without this number.
- Replacement carton and packaging can be purchased from KRK Systems, LLC. for \$18.00 each.
- For replacement part quotes call 818-534-1580.

Specifications

RP5

Frequency Response 53Hz -20kHz +/- 2.0dB
 High Frequency Driver 1" Soft Dome
 Low Frequency Driver 5" Aramid Glass Fiber
 Cabinet Dimensions(HxWxD) 10 7/8" x 7 1/4 x 8 7/8" 12 11/16" x 8 7/8 x 10 1/2"
 28 cm x 19 cm x 23 cm 38 cm x 27 cm x 31 cm
 Net Weight (each) 16 lbs. 23 lbs.

AMPLIFIER

Power Rating (HF/LF) 15 watts / 30 watts 18 watts / 50 watts
 Signal to Noise (HF/LF) 82dB / 90dB 84dB / 95dB
 T.H.D (HF/LF) .05% / .02% .09% / .01%
 Input Impedance
 Balanced 10K Ohm 10K Ohm
 Unbalanced 10K Ohm 10K Ohm
CROSSOVER
 Crossover Frequency 3.0KHz 2.6KHz
 Subsonic Filter 45Hz 40Hz
 FUSE 5mm x 20mm 1A 1.6A
 100V - 120V 500mA 800 mA
 220V - 240V

FEATURES
 XLR & 1/4" TRS Connectors
 RCA Connector
 IEC Mains Connector
 System Volume Control
 LED Power Indicator

Specifications

RP8

Frequency Response 45Hz -20kHz +/- 1.5dB 36Hz -50kHz +/- 1.5dB
 High Frequency Driver 1" Soft Dome
 Low Frequency Driver 8" Aramid Glass Fiber 10" High Excursion Glass Aramid Composite Woofer
 Cabinet Dimensions(HxWxD) 15" x 10 7/16 x 12" 15" x 14 x 15 11/16"
 38 cm x 27 cm x 31 cm 38.2 cm x 35.5 cm x 39.8 cm
 Net Weight (each) 30 lbs. 42 lbs.

AMPLIFIER

Power Rating (HF/LF) 20 watts / 70 watts 150 watts RMS
 Signal to Noise (HF/LF) 86dB / 97dB 98 dB
 T.H.D (HF/LF) .09% / .01% .05%
 Input Impedance
 Balanced 10K Ohm 10K Ohm
 Unbalanced 10K Ohm 10K Ohm
CROSSOVER
 Crossover Frequency 2.4KHz
 Subsonic Filter 35Hz
 FUSE 5mm x 20mm 2A 3.15A
 100V - 120V 1A 1.6A
 220V - 240V

FEATURES
 XLR & 1/4" TRS Connectors
 RCA Connector
 IEC Mains Connector
 System Volume Control
 LED Power Indicator