



NOTES: - ALL RESISTORS IN OHMS $\frac{1}{2}$ W 10% UNLESS OTHERWISE SPECIFIED.
 - ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.
 - DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000 Ω PER VOLT VOLTMETER.
 - NUMBERS IN PARENTHESES REFER TO AMPEX PART NO.
 - PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY. THE P.T. FOR 240V MODELS HAS BLACK WIRE CONNECTED TO BLUE WIRE
 - DC VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
 - D7-D10 ARE SILICON AN TYPE 1AMP 1400 VOLTS DIODES.

MODEL V2
 U.S. PATENT PENDING.

ampeg
 454 LODE DRIVE - 113 3RD AVE
 LYNN, NEW JERSEY

DRN BY	DATE	DWG. NO.	PART NO.	REV.
LC	671	06800	400268	B