



- T1 - GA-40P, 650V C.T. @ .120A, 6.3V C.T. @ 3.25A, 5v @ 2.0A
 T2 - Z3533, 10,000 ohm Pri., 6 to 8 ohm Sec.
 L1 - GA25C, 10 henry @ .120A
 L2 - E1896, 30 henry @ .030A
- CONDENSERS**
 C1, C4, C15 - 20 mfd, 25 volt Elec
 C20 - 40 mfd, 150 volt Elec
 C10, C11, C17 - 10 mfd, 450 volt Elec
 C16 - 20 mfd, 450 volt Elec
 C7, C8 - .001 mfd, 400 volt
 C3 - .01 mfd, 400 volt
 C6, C12, C18, C19 - .02 mfd, 400 volt
 C2, C5, C9, C13, C14 - .05 mfd, 400 volt
- RESISTORS**
 R28 - 150 ohm, 10 watt, wirewound
 R19 - 1K, 1 watt
 R27 - 10K, 1 watt
 R18 - 47K, 1 watt
- RESISTORS, 1/2 WATT**
 R4, R10, R30 - 1K
 R37 - 9.1K +/- 5%
 R23, R24 - 47K
 R38 - 51K +/- 5%
 R5, R6, R7 - 100K
 R2, R8, R13, R14, R20 - 270K
 R31, R32, R35, R36 - 330K
 R15, R17, R25, R26, R29 - 470K
 R1, R3, R9, R21, R22, R33, R34 - 1Meg
 R39 - 2.2Meg
- RESISTORS, VARIABLE**
 R11, R12 - 500K, Audio Taper
 R16 - 2Meg, Linear Taper

GA-40 1954

