

## SPECIFICATIONS

**Output Power<sup>2, 3</sup>:**

2 ohms, 1 kHz, 1% THD	250 W RMS per channel
4 ohms, 1 kHz, 1% THD	210 W RMS per channel
8 ohms, 1 kHz, 1% THD	130 W RMS per channel

**(Bridge mode, mono)**

4 ohms, 1 kHz, 0.1% THD	500 W RMS
8 ohms, 1 kHz, 0.07% THD	420 W RMS <i>- 578 V</i>

**Rated Output Power<sup>2</sup>:**

4 ohms, 20 Hz to 20 kHz, 0.1% THD	200 W RMS per channel
8 ohms, 20 Hz to 20 kHz, 0.07% THD	120 W RMS per channel

**Slew Rate<sup>3</sup>:**

Stereo mode, each channel	20 volts per $\mu$ Sec
Bridge mode, mono	40 volts per $\mu$ Sec

**Total Harmonic Distortion<sup>2, 3</sup>:**

20 Hz to 20 kHz, @ rated output power, 8 ohms	Less than 0.07%
---	-----------------

**Input Sensitivity & Impedance<sup>4</sup>:**

@ rated output power, 8 ohms	1.0 V RMS (0 dBV)
	20 K ohms (32 dB gain)

**Dimensions & Weight:**

Height	5.25" (13.3 cm)
Width	19" (48.3 cm)
Depth	9" (38.1 cm)
Weight	29 pounds (13.2 kg)

**Frequency Response<sup>2, 3</sup>:**

±1 dB, 1 W RMS, 8 ohms	10 Hz to 40 Hz
±0.2 dB, @ rated output, 8 ohms	20 Hz to 20 kHz

**Damping Factor<sup>2, 3</sup>:**

8 ohms, 1 kHz	Greater than 300
---------------	------------------

**Hum & Noise<sup>2</sup>:**

Below rated output power, 8 ohms	100 dB, unweighted
----------------------------------	--------------------

**Power Consumption<sup>2</sup>:**

@ rated output power, 8 ohms	4.4 A @ 120 V AC
------------------------------	------------------

**Cooling System:**

2-speed fan

**DDT™ Compression System:**

Switchable with LED

<sup>1</sup> @ 120 V AC, 60 Hz    <sup>2</sup> Stereo mode, both channels driven    <sup>3</sup> Typical Value    <sup>4</sup> Input attenuator set FCW