

Groove Tubes Specifications:

SFX SPACESTATION™ MK2 STEREO AMPLIFIER



SFX: The Cure For the Common Gig

The GT SFX Spacestation MK2 is a single compact powered monitor that creates a 300-degree field of stereo sound using a 100-watt per channel Class D power amp and dipole speaker array. The SFX "acoustical space vortex" created by the dipole speaker is the secret to the stereo magic, electronically encoding left and right signals, and then acoustically decoding them in the unique Front & Side powered speaker systems.

The SFX Spacestation MK2's front speaker is a custom-made co-ax speaker with a compression driver and super tweeter. The Side speaker is a specially designed full range speaker mounted 90 degrees off axis to the front speaker. Level and Width controls allow balance between the Front and Side speakers to compensate for room acoustics (use more Width for a dead room). The SFX MK2 also offers a Subwoofer output to handle larger gigs. The improvements over the original SFX models include a new 2-inch port in the cabinet for extended low end frequency response, as well as a re-tuning of the cabinet itself, adding smoother, more natural low frequency harmonics and increasing speaker life while allowing more power output. In the amplifiers' electronics, a new heavy-duty passive crossover and a new active EQ filter combine with its new front coaxial speaker for more power, tighter definition, and smoother frequency response at all volume levels.

The SFX Spacestation MK2 is perfect for amplifying stereo sources such as keyboards, and can also be driven from the stereo outputs of a mixer, or even directly from many stereo effects devices. Plug in and get a fantastic 300 degree stereo sound field for your vocals, keyboards, bass, and guitar which all emanates from one central point... so everybody hears the same mix, even the audience! The SFX Spacestation MK2 measures just 18" high and 11" deep and wide, and weighs only 32 lbs. It's the perfect solution for getting terrific, room-filling sound at small gigs!

SFX is a registered trademark of FMIC. US patent 6219426-B1.

SFX SPACESTATION MK2	SPECIFICATIONS
Inputs	Two 1/4" phone jacks for stereo signal input. SFX 100 Only: XLR mic input with 10dB pad and +48V phantom power
Input Levels	Line level (-10dBu to +10dBu)
Output	One 1/4" phone jack to drive line level external subwoofer amplifier
Power	100 + 100 Watts RMS into internal speaker loads
Distortion	0.009% typical, 0.1% maximum THD
Frequency Response	60Hz - 20kHz useable
Dimensions	18"H x 11"W x 11"D (45cm H x 28cm W x 28cm D)
Weight	32 lbs. (12.7kg)
Electrical	120 VAC, 3A (240 VAC, 1.5A)

SFX MK2 FEATURES:

- Great-sounding STEREO amplification from a single cabinet
- Compact and lightweight: only 18" x 11" x 11", 32 lbs.
- Heavy duty strap handle
- Stereo 100W/channel Class D power amp
- Patented SFX encoder for 300° stereo soundfield
- Front speaker system: 8" coax with 1" compression driver and super tweeter
- Master Level and stereo width controls
- Subwoofer output (automatically cuts off internal speakers at 100Hz when activated)

www.groovetubes.com

