81357

CHANNEL A/B

NOTES:

*1 : PART CAN BE REPLACED WITH 2SA1084 E

AC VOLTAGE 1000 HZ, MEASURED WITH VTVM

DC VOLTAGE MEASURED WITH VOLTMETER 100kOHM/V

FADER IN RATED POSITION (0dB)
ADDITIONAL GAIN WITH FADER IN MAX. POSITION

SAFETY COMPONENT
(MUST BE REPLACED BY ORIGINAL PART)

RATED CONDITIONS:

GAIN POTS MIN. OR MAX.
ALL POTS IN CENTER-POSITION
ALL FADERS AT 0dB
MASTER-FADER-L/R AT +6dB

NE5532 TL072 — LM2901 — 2SB737 2SA1084E — BC550

JS1A line mic — JS2A line — JS1B mic — JS2B line

LO-CUT — S1A-A — S1B-B

gain — Q1A Q2A Q3A Q4A Q5A — 2SA1084 — 2N3906 — 1N4148

VOICE FILTER — S2A-B — S2B-A — MC33178

insert — JS4A — JS4B

MID — VR2A-A — VR2B-A — FREQ — VR3A-A — VR3B-A — LO — VR5A-A — VR5B-A — HI — VR4A-A — VR4B-A

MUTE — S3A-A — S3B-A — PFL1 — PFL2 — PREFAD1 — PREFAD2

PFL — S4A-A — S4B-A — PFL-MONO — PFL-CON — LED-MS-A — LED-MS-B

PAN — VR7A-A — VR7B-A — VR8A-A — VR8B-A — VR9A-A — VR9B-A — VR10A-A — VR10B-A — VR11A-A — VR11B-A

MASL — MASR — FX1/AUX1 — FX2/AUX2 — AUX3PRE — AUX3POST — AUX4PRE — AUX4POST — SENSEAUX1-2 — SENSEAUX3-4 — BUS-REF

CN3-3 CN3-4 CN1-3 CN1-4 CN1-5 CN1-6 CN1-7 CN3-1 CN3-2 CN3-13 CN3-14 CN1-1 CN1-2 CN1-8 CN1-9 CN3-12 CN3-11 CN3-10 CN3-9 CN3-8 CN3-7 CN3-6 CN3-5 CN1-10

ALTERATIONS RESERVED!

				Last modified: 25.10.2004 09:21:37	81357D
				Last plotted: 19.01.2005 14:29:59	
				DATE / NAME	CIRCUIT DIAGRAM 1/3
				DSG'D 10.2003 Lang F.	
				CHK'D	362 338
				APP'D	2-
A	083/04	10.04	Lang	EVI AUDIO	PM1000/PM1600 -2
ISSUE	REVISION	DATE	NAME		