



- NOTES:
1. ALL COUPLING CAPACITORS MPC TYPE
 2. ALL POWER SUPPLY FILTER CAPS 105C TYPE
 3. WIRE TYPE FOR 8+ AND FILAMENTS 105C, TEFLON PREFERRED
 4. ALL TUBES 12AX7A TYPE
 5. ALL POWER TUBES SHOULD BE REPLACED IN TESTED PAIRS
 6. OBSERVE DIFFERENT GROUND POTENTIALS
 7. DISCHARGE ALL POWER SUPPLY POINTS BEFORE SERVICING
 8. ALL MEASUREMENTS TAKEN AT NOMINAL MAINS VOLTAGE
 9. ALL MEASUREMENTS ±1% 200K
 10. TEST SIGNAL 100V, 20 VOVV AC AT 1000/20
 11. BOOST PREAMP FOR 2 VOLTS AC AT 1000/20
 12. SET PRESENCE CONTROL AT 1
 13. TP41 BRAS ADJUST -3700C EL-34, -47 0L00C, -52 0S50A
 14. NEVER USE CHINESE OUTPUT TUBES (MECHANICALLY UNSTABLE)

DRAWN BY PAUL E. RIVERA
 LAST REV: 06.13.2011
 REV 3.2



Venus 5 Guitar Amplifier
 GUITAR AMPLIFIER