CH.2 EQ CONTROLS

FOOTSWITCH JACK

FOOTSWITCH FS-7
ASSEMBLY P/N 905-01

SEMKO/VDE 230VAC 50 Hz

NORTH AMERICA/CSA 115VAC 60Hz

MITI 100 VAC

CH.1 = RED
BOOST = ORANGE
NINJA = YELLOW

SIGNAL GROUND

NOTES:
1. ALL COUPLING CAPACITORS MPC TYPE
2. ALL POWER SUPPLY FILTER CAPS 105C TYPE
3. WIRE TYPE FOR B+ AND FILAMENTS 105C, TEFLON PREFERRED
4. ALL TRIODES 12AX7A TYPE
5. ALL POWER TUBES SHOULD BE REPLACED IN TESTED PAIRS
6. OBSERVE DIFFERENT GROUND POTENTIALS
7. DISCHARGE ALL POWER SUPPLY POINTS BEFORE SERVICING
8. ALL MEASUREMENTS TAKEN AT NOMINAL MAINS VOLTAGE
9. ALL MEASUREMENTS +/- 20%
10. TEST SIGNAL 1kHz, 25 mVAC AT PREAMP INPUT
11. ADJUST PREAMP FOR 2 VOLTS AC AT TP31/32
12. SET PRESENCE CONTROL AT 1
13. TP41 BIAS ADJUST: -37VDC EL-34, -47 6L6GC, -52 6550A
14. NEVER USE CHINESE OUTPUT TUBES MECHANICALLY UNSTABLE

DRAWN BY PAUL E. RIVERA
LAST REV: 03.02.93

Rivera Research & Development

R-SERIES GUITAR AMPLIFIER

50/55/100W MODELS C:\ACAD\SCHEM\RSERIES