



**CAUTION** 500 VOLTS AVAILABLE DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS FOR BLEEDERS TO DISSIPATE B+ VOLTAGE

FENDER MUSICAL INSTRUMENTS  
 CBS MUSICAL INSTRUMENTS  
 A DIVISION OF CBS INC.  
 FULLERTON, CALIFORNIA  
 U.S.A.

**TEST DATA**

(MV) DENOTES TYPICAL 1K HZ SIGNAL FOR 10 WATT OUTPUT (WITH PLUS INTO INPUT JACK) (USE 0.1 MFD 600 CAPACITOR IN SERIES WITH GENERATOR'S "HOT" LEAD)  
 CONTROL SETTINGS - EQUALIZERS AT MID POSITION  
 PRESENCE AT MINIMUM  
 OTHERS AT MAXIMUM

D.C. VOLTAGES READ WITH NO SIGNAL INPUT

1. USED IN SOME PLACES  
 2. ALL RESISTORS 1/2 W. 10%  
 ALL CAPACITORS AT LEAST 100 P.P.M.  
 NOTES: UNLESS OTHERWISE SPECIFIED

SAMPLES OF FIRST ARTICLE PARTS MUST BE APPROVED BY FENDER, ROGERS, RHODES R & D ENG. BEFORE STARTING PRODUCTION

HEAT TREATMENT	UNLESS OTHERWISE SPECIFIED TOLERANCES	DWN	DATE
	FRACTIONS = ± 1/32	CHK	
	XX = ± 0.10	APPD	
	ANGLES = ± 1/2°	E.E.	
ROCKWELL			
	FRAC.IONS - WOOD = ± 1/16		
	HOLE'S - CORED = ± .005 - .000		
	BEND ANGL'S = ± 1°		
	HOLE'S - DRILLED & PIERCED = ± .0025 - .001		
	SOFT ANGL'S = MAX.		
	STRAIGHTENING		
	UNMARKED ANGL'S ARE 90°		
	UNLESS OTHERWISE SPECIFIED		

Fender/Rogers/Rhodes  
 CBS MUSICAL INSTRUMENTS - A DIVISION OF CBS INC.  
 FULLERTON, CALIFORNIA 92701  
 PART NAME: SCHEMATIC - 200 WATT BASS AMPLIFIER W/LED  
 RELEASE: [ ] DATE: [ ]  
 SCALE: [ ] MODEL: [ ]  
 PART NO: [ ]