



CAUTION 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS MINIMUM FOR BLEEDERS TO DISSIPATE B+ VOLTAGES.

TEST DATA
 MV DENOTES TYPICAL 1K Ω SIGNAL FOR 10 WATTS OUTPUT AND 450MV REVERB INPUT UNIT DRIVE
 (A) INSERT BLANK PLUG INTO INPUT JACK FOR THIS TEST.
 CONTROL SETTINGS- EQUALIZERS AT MID POSITION. DISTORTION PRESENCE AT MINIMUM. OTHERS AT MAXIMUM.

XA-USE 0.1MFD 600V CAPACITOR IN SERIES WITH GENERATOR.
 D.C. VOLTAGES READ WITH NO SIGNAL INPUT AND DISTORTION OFF²

(A) 035604 CONDUCTS WITH DISTORTION ON³.

FENDER MUSICAL INSTRUMENTS

CBS MUSICAL INSTRUMENTS
 A DIVISION OF CBS INC
 FULLERTON CALIFORNIA
 U.S.A.

3. USED IN SOME VERSION.
2. ALL RESISTORS ARE 1/2W, 10%.
1. ALL CAPACITORS AT LEAST 600 V.D.C.

NOTES: UNLESS OTHERWISE SPECIFIED

Fender/Rosen/Rhodes
 - SCHEMATIC -
 180 WATT
 SUPER TWIN REVERB
 013606