



**NOTES** - ALL RESISTORS IN OHMS 1/2W 10% UNLESS OTHERWISE SPECIFIED.  
 - ALL CAPACITORS IN MFD AND 400V 10% UNLESS OTHERWISE SPECIFIED.  
 - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20,000 Ω PER VOLT VOLTMETER - NUMBERS IN PARENTHESES REFER TO AMPEG'S PART NO. \* 2A FUSE SHOULD BE IN 240V MODELS ONLY.  
 - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO GROUND UNLESS OTHERWISE SPECIFIED.  
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.  
 \*\* RES. 60, 61, 62, 63 & 64 ARE LOCATED ON SW1.  
 \* - THE P.T. FOR 240V MODELS HAS BLK WIRE CONNECTED TO BLUE WH. AS DOTTED LINE SHOWS

MAGNAVOX NO. 5917-1

	<b>MODEL B15S</b> U.S. PATENT PENDING				
	DRAWN BY S. C.	DATE 3-71	DWG. NO. 06400	PART NO. 40102580	REV. D