



- ⊗ 55W MODELS
- ⊙ 100W MODELS
- ⊕ CSA VERSIONS
- ⊖ NEMKO/CB VERSIONS

- NOTES:
1. ALL COUPLING CAPACITORS MPC TYPE
  2. ALL POWER SUPPLY FILTER CAPS 105C TYPE
  3. WIRE TYPE FOR B+ AND FILAMENTS 105C, TEFLON PR
  4. ALL TRIODES 12AX7A TYPE
  5. ALL POWER TUBES SHOULD BE REPLACED IN TESTED
  6. OBSERVE DIFFERENT GROUND POTENTIALS
  7. DISCHARGE ALL POWER SUPPLY POINTS BEFORE SERV
  8. ALL MEASUREMENTS TAKEN AT NOMINAL MAINS VOLT.
  9. ALL MEASUREMENTS +\ - 20%
  10. TEST SIGNAL 1kHz, 25 mVAC AT PREAMP INPUT
  11. ADJUST PREAMP FOR 2 VOLTS AC AT TP31/21
  12. SET PRESENCE CONTROL AT 1
  13. TP41 BIAS ADJUST: -37VDC EL-34, -47 6L6CC, -5
  14. NEVER USE CHINESE OUTPUT TUBES.MECHANICALLY