



- ▶ Overall dimensions : 120 mm x 120 mm x 38 mm (depth).
- ▶ Magnet weight : 700 g.
- ▶ Magnet dimensions : 96 mm diam. x 33 mm.
- ▶ Voice coil : Alu former, 20 mm diam.
- ▶ Emissive surface : 30 mm diam. inverted pure Titanium dome.
- ▶ Suspension : Supronyl, positive half roll profile.




Specifications	
Rated power handling	
Nominal/Program (W)	12/100
Voice coil	
Diameter/Length (mm)	20/2.2
Nom./Mini impedance (Ω)	8/7
DC resistance (Ω)	6
Inductance (mH)	0.1
Former	Aluminium
Layers	2
Wire	Copper
Cone	Titanium
Surround	Supronyl
Magnet	
Diameter (mm)	96
Weight (g)	700
Flux density = B (T)	1.85
Gap height (mm)	2
Sensitivity	
2.8V/1 m (dB)	94
Net weight (kg)	1.400
Xmax (mm)	—

On axis and 30° off axis frequency response



Impedance magnitude and phase versus frequency



Parameter	Value
Fs (Hz)	602.3
Qts	0.656
Qes	0.827
Qms	3.18
Rcc (Ω)	6.05
Zmax (Ω)	33.2